



SPECIFICATIONS

MATERIAL:

INSULATOR: POLYAMIDE 6.6, BLACK,
 RATED UL 94V-0
 CONTACTS: BRASS, 0.8T, TIN PLATED
 SCREWS: STEEL, NICKEL PLATED

ELECTRICAL:

OPERATION VOLTAGE: 300 V MAX
 CURRENT RATING: 15 AMPS
 INSULATION RESISTANCE: 1000 MΩ MIN
 @500V DC BETWEEN ADJACENT CONTACTS
 (75°F AND 50% R.H.)
 DIELECTRIC WITHSTANDING VOLTAGE: 2000V AC
 MIN RMS (SEA LEVEL)

MECHANICAL:

WIRE RANGE: 22 - 16 AWG
 OPERATING TEMP: -40°C TO + 105°C

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SPI, AND SHALL NOT BE COPIED, USED OR REPRODUCED WITHOUT PERMISSION.

DIMENSIONS ARE IN IN. [MM]
 UNLESS NOTED
 TOLERANCES ARE:
 .XX ±.01
 .XXX ±.005
 ANGLES ± 1°



1170 S. PATTON ST.
 XENIA, OHIO 45385
 PH: (937) 374-2700
 FX: (937) 374-4774

DR HEATHER JOHNSON	
APV'D	SAW
DATE	12/12/97
PAGE	1 OF 1

TITLE	9 POSITION TERMINAL BLOCK WITH 6-32 SCREWS	
SCALE	PART NO.	REV.
NTS	TB21-1B09NT/2 (7120030-119)	A