



**SPECIFICATIONS:**

**Material:**

Insulator: Polyester, black, rated UL94V-0  
 Contacts: Brass, 1.2t, gold plated  
 Screws: Steel, gold plated

**Electrical:**

Operation voltage: 300V AC max  
 Current rating: 30 Amps max  
 Insulation resistance: 1000 MW min  
 @500V DC between adjacent contacts  
 (75°F and 50% R.H.)  
 Dielectric withstanding voltage: 1500V AC  
 min rms (sea level)

**Mechanical:**

Wire range: 22-12 AWG  
 Operating Temperature: -40°C to + 105°C

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SPI, AND SHALL NOT BE COPIED, USED OR REPRODUCED WITHOUT PERMISSION.

DIMENSIONS ARE IN IN. [MM]  
 UNLESS NOTED  
 TOLERANCES ARE:  
 .XX ±.01  
 .XXX ±.005  
 ANGLES ± 1°



1170 S. PATTON ST.  
 XENIA, OHIO 45385  
 PH: (937) 374-2700  
 FX: (937) 374-4774

DR HEATHER JOHNSON	
APV'D	DATE
	05/07/98
PAGE	1 OF 1

TITLE	
SIDE MOUNT 3 WALL BARRIER REVERSE RIGHT ANGLE TERMINAL BLOCK	
SCALE	PART NO.
NTS	TB41-F08F
REV.	